

Spiro-Lox[™] – Triple Wound Locks for Floating Pins (one piece)

Set Part #	Description Pcs pe	r Set
12084	Wire Lock .084"	1
927074	Spiro-Lox .074" for Small Block Pins (.927")	2
990042	Spiro-Lox .042" for Big Block Pins (.990")	4
990074	Spiro-Lox .074" for Big Block Pins (.990")	2
W5075	Wire Lock .072" for Small Block (.927")	2

Wrist Pin Wire Lock Installe

One of our favorite customers invented this handy tool for ease of lock installation. They are available in steel or a disposable plastic version for your tool box at the track.



Part # Description S-927 SB Spiro-Lox Installer S-990 BB Spiro-Lox Installer W-927 SB Round Wire Installer W-990 BB Round Wire Installer

Wrist Pin Bushings

Part #	O.D.	I.D.	Length	
912-01	.991"	.912"	1.015"	Lentz
926-01	.976"	.926"	1.060"	Carrillo
926-02	.991"	.926"	1.000"	GM
926-03	1.000"	.926"	1.000"	Crower
926-04	.976"	.926"	1.025"	BRC
926-05	.990"	.926"	1.050"	Manley
926-06	.976"	.926"	1.125"	Carrillo (Buick Rod)
926-07	1.005"	.927"	1.015"	
926-08	.975"	.920"	1.155"	MGP
926-09	.990"	.925"	1.025"	
980-01	.980"	.926"	1.000"	
985-01	1.052"	.985"	1.125"	BRC (Big Block)
985-02	1.041"	.985"	1.125"	Carrillo/Manley (Big Block)
985-03	1.050"	.985"	1.305"	
985-04	1.097"	.985"	1.125"	
985-05	1.055"	.985"	1.265"	

Ultimate replacement

We have found that many problems with the wrist pin start with the rod bushing. Our bushings are made from the best bronze alloys available. Whether you are replacing rod bushings or changing your pin location, we have the bushing you need. Custom sizes are available.



Recommended press: .003" to .005"